

IMAGE PROCESSING APPARATUS, IMAGE PROCESSING
METHOD, AND RECORDING MEDIUM

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority from Japanese Application No. P2000-144410 filed May 17, 2000.

BACKGROUND OF THE INVENTION

[0002] The present invention relates to an image processing apparatus, an image processing method, and a recording medium, and particularly to an image processing apparatus, an image processing method, and a recording medium in which the display setting of image quality is automatically changed so that the program of a received television broadcast can be always displayed at optimum image quality.

[0003] In recent years, digital broadcasting has begun in earnest. In digital broadcasting, data such as an image or sound is compressed by an MPEG (Motion Picture Experts Group) system or the like and is broadcast.

[0004] In digital television broadcasting, since the data is compressed, as compared with analog television broadcasting, a multi-channel and high quality content (program) can be broadcast.

[0005] In a conventional television receiver, the function of setting various image qualities is added, and the image quality can be adjusted according to the taste of a user. When many kinds of contents, such as still images and character figures, in addition to normal moving images, come to be broadcast by the development of digital television broadcasting, a more diversified and delicate image quality adjustment is desired.

[0006] However, since the setting of image quality in the conventional television receiver is performed by a manual operation while a user confirms a displayed image with the naked eye, delicate setting becomes difficult, and eventually, the user does not adjust the image quality for each program,

but usually watches all programs at the same image quality. As a result, there has been a problem that a high-grade function of the television receiver can not be sufficiently exhibited.

SUMMARY OF THE INVENTION

[0007] The present invention enables a user to always watch a program at optimum image quality by automatically changing the setting of a screen display in accordance with the program.

[0008] An image processing apparatus of the present invention includes an extraction unit operable to extract image data of a selected program, an acquisition unit operable to acquire image encoded information of the selected program, and a setting unit operable to set a signal processing parameter for processing an image signal of the program in accordance with the image encoded information.

[0009] The extraction unit may extract the image data of the selected program from a transport stream, and the acquisition unit may acquire the image encoded information of the selected program from service information included in the transport stream.

[0010] The image processing apparatus of the present invention can further include a storage device operable to store the signal processing parameter for processing the image signal.

[0011] The image processing apparatus of the present invention can further include changing means for changing the signal processing parameter on the basis of an input from a user.

[0012] An image processing method of the present invention includes extracting image data of a selected program, acquiring image encoded information of the selected program extracted in the extracting step, and setting a signal processing parameter for processing an image signal of the selected program in accordance with the image encoded information.

[0013] A recording medium of the present invention is recorded with a computer readable program for processing images. The program includes extracting image data of a selected program, acquiring image encoded information of the selected program extracted in the extracting step, and setting a signal processing parameter for processing an image signal of the selected program in accordance with the image encoded information.

[0014] In the image processing apparatus, the image processing method, and the recording medium according to the present invention, the signal processing parameter for controlling the display of a picture of the program is set in accordance with the image encoded information of the selected program. Accordingly, it becomes possible to watch the program easily at the optimum screen quality without carrying out a complicated operation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1 is a block diagram showing a structural example of a television receiver to which the present invention is applied;

[0016] FIG. 2 is a flowchart for explaining the operation of the television receiver of FIG. 1;

[0017] FIG. 3 is a view showing an example of MPEG video encoding parameters; and

[0018] FIG. 4 is a block diagram showing a structural example of another television receiver to which the present invention is applied.

DETAILED DESCRIPTION

[0019] FIG. 1 shows a structural example of a television receiver 1 which receives a digital broadcast transmitted from a not-shown broadcasting station and displays (outputs) an image and sound.

[0020] An IF demodulator 2 demodulates an IF (Intermediate Frequency) signal obtained from a digital broadcast wave

received by a not-shown antenna and outputs it as a transport stream to a demultiplexer 4.

[0021] In addition, a transport stream transmitted from a CATV system, a network system or the like is supplied to the demultiplexer 4 through a transmission path 3.

[0022] The demultiplexer 4 separates a TS (transport stream) packet including image data from TS packets constituting the supplied transport stream, and outputs it to an MPEG video decoder 5.

[0023] The TS packet holding the image data is decoded in the MPEG video decoder 5, and is output to an image signal processing portion 6. Additionally, MPEG video encoding parameters indicating information relating to the encoding of the TS packet are separated in the MPEG video decoder 5 and are output to a CPU (Central Processing Unit) 8.

[0024] The image signal processing portion 6 generates an RGB signal from a decoded luminance signal and color-difference signal, and displays an image on an image display portion 7 including a CRT (Cathode-Ray Tube) or an LCD (Liquid Crystal Display).

[0025] The CPU 8 controls respective portions in response to an input from a user interface 10 so as to output a signal corresponding to an operation of a user. Data and programs necessary for the CPU 8 to execute various processes are stored in a RAM 9.

[0026] An HDD (Hard Disk Drive) 102, a ROM (Read Only Memory) 103, and a drive 104 are connected to the CPU 8 through a bus 101. As a recording medium, a magnetic disk 111, an optical disk 112, a magneto-optical disk 113, or a semiconductor memory 114 is mounted on the drive 104.

[0027] Next, the operation of the television receiver 1 of FIG. 1 will be described with reference to the flowchart of FIG. 2.

[0028] At step S1, the IF demodulator 2 demodulates an IF signal obtained from a digital broadcast wave received by a not-shown antenna, generates a transport stream, and outputs it to the demultiplexer 4.

[0029] At step S2, the demultiplexer 4 separates a TS packet holding video data of an objective program from PSI (Program Specific Information) and SI (Service Information) included in the supplied transport stream, and outputs it to the MPEG video decoder 5. The PSI means specific information of a program (broadcast program) prescribed by the MPEG, and consists of four tables, including a PAT (Program Association Table), a PMT (Program Map Table), a NIT (Network Information Table), and a CAT (Conditional Access Table) and various descriptors. The SI is information which is unique to a broadcasting business.

[0030] At step S3, the MPEG video decoder 5 decodes the TS packet including the video data by the MPEG system, generates a luminance signal (Y) and color-difference (Cr, Cb) signals, and outputs them to the image signal processing portion 6. In the present invention, in order to cause the optimum image to be displayed on the image display portion 7, signal processing executed in the image signal processing portion 6 is controlled in accordance with the image signal processing parameters acquired by the CPU 8. Then, the MPEG video decoder 5 extracts the MPEG videos encoding parameters as shown in FIG. 3, which describe information in relation to the encoding of the video data, and outputs them to the CPU 8.

[0031] In an example of the MPEG video encoding parameters of FIG. 3, profile/level designation is MP/HL (Main Profile/High Level), the number of horizontal pixels is 1920, the number of vertical lines is 1080, an aspect ratio is 16:9 display, a bit rate is 22 Mbps, a frame rate is 30/1,001 Hz, a scan system is a sequential scanning (progressive scanning) system, a color initial value, a conversion characteristic,

and a matrix coefficient are prescribed values of ITU-R recommendation BT. 709, and a repeat first flag is a flag used at 2:3 pull down.

[0032] At step S4, the CPU 8 searches and sets image signal processing parameters corresponding to a combination of the MPEG video encoding parameters, which are supplied from the MPEG video decoder 5, from a correspondence table of the MPEG video encoding parameters and the image signal processing parameters which is previously stored in the RAM 9. For example, in the case where the combination of the supplied MPEG video encoding parameters is such that profile/level is MP/HL, the number of display pixels/frame rate is 1920 x 1080/24P, and the bit rate is 22 Mbps, the CPU 8 recognizes that the image data of the TS packet extracted from the transport stream is a movie of high image quality, and acquires and sets such image signal processing parameters as to lower the brightness, attenuate the sharpness, lower the color temperature, cut NR (Noise Reduction), cut VM (Velocity Modulation (beam velocity modulation)), and strengthen gamma correction, from the correspondence table of the combination of the MPEG video encoding parameters and the image signal processing parameters stored in the RAM 9. On the basis of these image signal processing parameters, the CPU 8 controls the signal processing in the image signal processing portion 6 so that all of a delicate gradation of a dark portion, a profile, and color can be displayed with a soft touch, and the quality of an original film can be displayed.

[0033] At step S5, on the basis of the image signal processing parameters set by the CPU 8, the image signal processing portion 6 processes the luminance signal and the color-difference signals supplied from the MPEG video decoder 5, generates an RGB signal, and outputs it to the image display portion 7.

[0034] At step S6, the image display portion 7 displays an image on the basis of the RGB signal supplied from the image signal processing portion 6.

[0035] In the above operation, although the signal processing in the image signal processing portion 6 is controlled on the basis of the image processing parameters, it is also possible to further control the image display portion 7, as shown in FIG. 4.

[0036] In the present invention, it is also possible to change the setting of the image signal processing parameters for a particular program (series program) according to the taste of the user through operation of the user interface 10. The changed image signal processing parameters for the program are stored in the RAM 9. Thereafter, when the same program is selected by the user, the signal processing in the image signal processing portion 6 and the image display portion 7 are controlled on the basis of the image signal processing parameters stored for that program, and the image is displayed.

[0037] The present invention can also be applied to an audio signal. For example, in the case where signal processing as to data of a music program is carried out, with respect to a video signal, the above described image signal processing is carried out and is displayed, and with respect to the audio signal, sound signal processing parameters are set from a combination of MPEG audio encoding parameters, and a sound signal processing portion and a sound output portion can be controlled as well.

[0038] Further, in the case where a plurality of images are displayed in a plurality of windows of one screen at the same time, a display (output) may be controlled for each of the images displayed in the respective windows.

[0039] Although the description above has been made in the case where the present invention is applied to a television

receiver, the present invention can be applied to any devices (for example, a personal computer, etc.) which process digital data, including an IRD (Integrated Receiver/Decoder).

[0040] Although the foregoing series of processes can be executed by hardware, they can also be executed by software. In the case where the series of processes are executed by software, a program constituting the software is installed from a recording medium to a computer integrated in dedicated hardware, or, for example, a multi-purpose personal computer which can execute various functions by installing various programs.

[0041] As shown in FIG. 1, this recording medium consists not only of a package medium which is separate from a computer and is distributed to the user to provide a program and in which the program is recorded, such as a magnetic disk 111 (including a floppy disk), an optical disk 112 (including a CD-ROM (Compact Disk-Read Only Memory) and a DVD (Digital Versatile Disk)), a magneto-optical disk 113 (including an MD (Mini-Disk)), or a semiconductor memory 114, but also by a ROM 103 or an HDD 102 which is provided to the user in the state in which it is previously integrated in the computer and in which the program is recorded.

[0042] Incidentally, in the present specification, steps describing the program recorded in the recording medium naturally include processes carried out in time series along the recited sequence, and also include processes which are not necessarily processed in time series but are executed in parallel or individually.

[0043] Besides, in the present specification, the system indicates an entire apparatus constituted by a plurality of devices.

[0044] Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of

the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000